

POS PRINTER



SLK-TE25

- Front paper loading
- Front paper exit
- Spill-proof function : superior resistance to spill with a sealed top.
- High speed printing : 200mm/sec
- Paper width adjustable 80mm
- Easy to use & Innovative

APPLICATIONS



Shopping



Mart



Airport



Hospital



Coffee Shop



Bank



Restaurant



Ticketing



Parking



Lottery




Election



ADVANCED HIGH-SPEED & VERSATILE

SLK-TE25



MODEL		SLK-TE25
PRINTING	METHOD	Direct Thermal
	SPEED	Max. 200mm/sec
	WIDTH	72mm(512 Dots/Line)
	RESOLUTION	180DPI
PAPER	TYPE	Thermal Paper
	WIDTH	80mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. ø 83.0mm
	ROLL CORE INNER	12.5mm ± 0.5mm
RELIABILITY	TPH LIFE	160Km
	MCBF	60,000,000Lines
AUTO CUTTER		1,500,000cuts(Guillotine)
SENSOR	STANDARD	Paper End, Paper Low, Cover Open
	OPTION	Black Mark
INTERFACE		USB (B type) plus one more card selectable (Serial, Parallel, Wi-Fi, Ethernet, Bluetooth(iOS))
EMULATION		ESC/POS Command Compatible
DRIVER		Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 1.75A
TEMPERATURE	OPERATION	5 ~ 40°C
	STORAGE	-20 ~ 60°C
DIMENSION		112.5 x 200 x 125 mm (W x D x H)
WEIGHT		1.4kg
COLOR		Cool grey, Ivory

INTERFACE



ACCESSORY



Melody box



SEWOO TECH Co., Ltd.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 447-210 Republic of Korea

T. +82-31-8077-5000 F. +82-31-459-8880

www.miniprinter.com

